

Rugged stainless steel camera enclosure

STATON IP



High-quality camera technology requires high-quality protection, especially for outdoor use. The STATON stainless steel camera enclosure defies the most extreme weather conditions - over years.

In addition to its extreme weather resistance, the STATON IP convinces with its universal and time-saving mounting and connection options.

HIGHLIGHTS

- » Quick camera change without recalibration
- » Self-supporting camera / lens carrier with the possibility of adjusting the camera / lens unit when the camera unit is installed
- » Universal mounting (suspended or standing)
- » Static stainless steel camera enclosure including pan/tilt unit
- » Power supply via PoE+ possible
- » Minimal service and maintenance costs
- » Highest reliability and first-class investment protection
- » Optimally suited for use in traffic engineering and industry

TECHNICAL DATA

GENERAL DATA

Material:	stainless steel V4A 1.4571 (other material on request)
Protection class:	IP66
Security:	according to DIN EN 60950-1
Heating:	integrated, controlled windshield heating
Temperature range:	-25°C to +55°C
Mass:	approx. 4.8 kg (with joint and sunshield)
Standard surface:	blank (other surfaces optional)
Supply voltage:	PoE+, IEEE 802.3a + Class 4
Power consumption:	heater 10W / Camera max. 10W
Video:	Ethernet
Data:	Ethernet 10/100 Base-T

DIMENSIONS

Installation dimensions:	280 x 82 x 76 mm (LxWxH)
Enclosure:	418 x 106 x 123 mm (LxWxH)
incl. sunshield and joint:	438,5 x 126 x 206 mm (LxWxH)
incl. sunshield, joint system connector and cable bending radius:	605,5 x 126 x 206 mm (LxWxH)

ACCESSORIES & ORDER DATA

	Stainless steel sunshield for Staton, standing, 1.4571 (V4A), 438.5 x 118 x 123mm (LxWxH)	GS24001		Stainless steel sunshield for Staton, suspended, 1.4571 (V4A), 438.5 x 118 x 123mm (LxWxH)	GS24002
	Cantilever for Staton, 385 mm, static, 1.4571 (V4A)	GS25664		Cantilever for Staton, 385 mm, variable tilt -18° to +82°, 1.4571 (V4A)	GS24002
	Stainless steel camera enclosure static with U-joint	GS25101		Adapter U-joint for cantilever 120mm	GS25668
	Cable connector field terminable for control cable, metal	BE41548		Control cable with RJ45	BE41547
	Cable connector field-terminable for control cables, plastic	ZK00853		System pole element, without clamping band, stainless steel 1.4571 (V4A)	GS25680