

PoE enclosure for outdoor applications

## WD-IP 350



The rugged aluminium camera enclosure WD-IP 350 protects your IP camera thanks to the integrated window heating and the sunshield from extreme weather conditions – reliable and over years.

Universal and timesaving mounting opportunities reduce installation, maintenance and service costs. That is the reason why the WD-IP 350 is ideally suited for using in outdoor areas.

### HIGHLIGHTS

- » Easy and fast mounting
  - data and power supply via Ethernet (PoE+)
  - quick camera change without recalibration
  - universal mounting (suspended or standing)
  - static camera enclosure including pan/tilt unit
- » Hidden cable routing protects against manipulation (optional)
- » Optimal use in outdoor areas
  - IP66
  - integrated window heating
  - sunshield optional
- » Minimal service and maintenance costs
- » High reliability and investment protection

## TECHNICAL DATA










### GENERAL DATA

Material:	aluminum, powder coated
Colour:	RAL9006
Protection class:	IP66
Security:	CE certification, EN62368-1, EN55032:2015, EN50130-4:2011
Heater:	regulated window heating
Operating temperature:	-25°C up to +55°C
Mass:	enclosure: approx. 4,2 kg cantilever arm: approx. 1,1 kg
Mounting:	suspended or stationary
Power supply:	PoE+, IEEE 802.3 at Class 4
Power consumption:	Camera: max. 10 W Heater: 10 W
Data cable:	Ethernet 10/100 Base-T, CAT 6A, S / FTP, PoE+, length 4m, UV-resistant, flameretardant, oil-resistant and halogen-free, open cable end, field assembly

### DIMENSIONS

Enclosure:	378 x 130,5 x 130,5 mm (LxWxH)
incl. sunshield:	450 x 149,9 x 140,5 mm (LxWxH)
incl. sunshield and joint:	450 x 149,9 x 214 mm (LxWxH)
incl. sunshield, joint and cantilever arm:	519,7 x 158,5 x 345,2 mm (LxWxH)

### ACCESSORIES & ORDER DATA

	Camera enclosure WD-IP, PoE, RAL9006	GS24500		Cantilever arm WD-IP 300mm, wall mounting, static, 1.1kg	GS25691
	Sunshield for WD-IP 350, standing, 450x149,9 mm (LxW), aluminium, RAL9006	GS24501		Mast mounting plate complete with clamps for WD-IP cantilever	GS25695
	Wall mounting plate for cantilever WD-IP	GS25692		Cover cable guide for U-joint	BE69214
	Cable connector, field assembly, metal	BE41548		Separately U-joint without cantilever WD-IP complete with screw set	GS25693
	Cable connector, field assembly, plastic	ZK00853			