

Data Radio Device for ETCS Purpose

EDOR 5E



RIU-ETCS – Funkwerk’s mobile solution for ETCS applications – in the standard version provides fully independent radio units EDOR-5E with state-of-the-art GSM-R mobile terminal MT5-E (8 watt) in combination with the integrated wide-range power supply covering the range of 24 to 110 V onboard voltage.

The EDOR-5E is compliant to latest specification for improved receiver parameters ETSI TS 102 933 V2.1.1.

EDOR-5E-MODULE

The EDOR 5E modules can be equipped with or without a data logger (EDOR 5E or EDOR 5E/D-LOG). The data logger is designed for raw data collection of the trace data from the fixed MT5-E radio modules inside the RIU-ETCS.

One or up to four modules EDOR 5E are contained in a approved and certified 19" standard rack.

The software of the radio module is based on the Release 04 GSM standard for operating in CS or PS mode.

ETCS

On an initiative of the EC, European Railways have introduced ETCS (European Train Control System) as the unified control system for train command and control for high speed traffic. This standard shall insure European interoperability with high reliable and safe operation, economic operation and increased speed and track capacity besides many other operational and technical benefits.

ETCS Level 1 is an overlay of the existing signalling systems with Eurobalises and track circuits. Levels 2 and 3 are supported via the GSM-R data communication.

The on-board equipment for level 2/3 requires in minimum two radio subsystems for GSM-R data calls independent to the GSM-R voice communication system.

TECHNICAL DATA

DIMENSIONS / WEIGHT

| | |
|--------|--------------|
| Width | 86 mm |
| Height | 129 mm (3HE) |
| Depth | 185 mm |
| Weight | 1,5 kg |

POWER SUPPLY

| | |
|-------------------------------|---|
| Nominal battery voltage range | 24 V to 110 V |
| Tolerances | 16.8 to 137.5 V |
| Supply type | floating |
| Stand-by power Idle Mode | 3.5 W |
| Maximum power GSM Mode | 10.3 W |
| GPRS Mode | 15.6 W |
| Connector | Phoenix PSC 1.5 / 5-M-PE protection class 1 |

ENVIRONMENTAL CONDITIONS

| | |
|-----------------------|-----------------------------|
| Operating temperature | -25 ... +70°C (EN 50155) T3 |
| Storage temperature | -40 ... +85°C |

DATA-INTERFACE

| | |
|-------------|---------------------|
| User (DATA) | V.24 / V.11 (RS422) |
| Service | V.24 / V.28 (RS232) |

TECHNICAL DATA

RADIO INTERFACE

| | |
|-----------------------|--|
| Frequency range | ER-GSM: TX 873-915 MHz RX 918-960 MHz ARFCN: 940-1023, 0-124 |
| Power transmission | 8 W +/- 2dB GSM Class 2 |
| Reference sensitivity | -104 dBm typically |
| Antenna connector | TNC female, 50 Ω |
| Multi-slot class 10 | CS-1, CS-2, CS-3, CS-4, MCS5-MCS9 |

GSM BEARER SERVICES

| | |
|-----------------------------------|--|
| according GSM 02.02 (ETS 300 501) | Transparent according to GSM 04.22 (ETS 300 053) |
| BS24 Asynchronous data 2.4 kbit/s | BS25 Asynchronous data 4.8 kbit/s |
| BS26 Asynchronous data 9.6 kbit/s | BS70 GPRS E-GPRS (EDGE) |

SUPPLEMENTARY SERVICES

| |
|--|
| CLIP, CoLP, UUS1, eMLPP |
| andere: OTDI, cOTDI, USSD, CLIR, CoLR, CFU, CFB, CFNRy, CFNRc, CW, HOLD, MPTY, CUG, AoCI, AoCC, BAOC, BOIC, BOIC-exHC, BAIC, BAIC-Roam |
| additional Funkwerk specific functions, e.g. acceleration network search |

DATALOGGER INTERFACE

| | |
|--------------------|-------------------------|
| GPS / Trace / ODO | 3 x 5-pole M9 connector |
| Ethernet connector | 4-pole M12 connector |

MISCELLANEOUS

| |
|---|
| Internal ARM based processor system |
| SW coded on Linux Operation System |
| 2 GB internal data memory on datalogger |