

GSM-R Cab Radio MESA 23

## MTRS 1 RSS



The MTRS 1 RSS is a terminal unit for the purpose of train radio, shunting radio and data applications which operates in GSM-R networks. It fulfils the European requirements for use in rail vehicles.

MESA 23: The universal system architecture contains uniform and standardised interfaces and sub-assemblies conceived as 19" plug-in printed circuit boards. Thereby an easy and fast exchange of the sub-assemblies is guaranteed.

The MTRS 1 RSS consists of the digital transmission and receiving device, the controls, the interface modules and the power supply. The CON/IFOT module controls the radio module, manages the priority of the calls, controls the operating devices, the additional data applications and the interface modules.

The terminal unit operates in the 900 MHz GSM frequency spectrum in the following frequencies::

- » Transmitting frequency range: 873 to 915 MHz
- » Receiving frequency range: 918 to 960 MHz

In joint operation with operating device MMIS, handsets and loudspeakers, the MTRS 1 RSS realises full train radio functionality.

This standard model can be equipped with the following assemblies:

- » IFS module with 2 serial interfaces for data transmission
- » IFS-A module with 1 serial interface for data transmission and 1 interface to connect external radio devices
- » UIC module for connecting to the train's internal UIC line according to UIC 568 (PA/Intercom)
- » IFT-N module for connecting to a data radio application
- » MT5E for data radio (results in: MTRS 1+1 RSS)

## TECHNICAL DATA

### DIMENSIONS / WEIGHT

Construction	Module rack (3 U / 84 HP)
Width	482.6 mm
Height	132.6 mm
Depth	193 mm
Weight	max. 7.5 kg

### POWER SUPPLY

Input voltage	nominal 24, 36, 48, 72 or 110 VDC
Tolerances	according to DIN EN 50155
Interruption	according to DIN EN 50155, Class S1 (no interruption)
Maximal input power	nominal 165 W (calculated)
Maximal power consumption	1.5 A to 6.9 A (depending on voltage 110 VDC to 24 VDC)

### ENVIRONMENTAL CONDITIONS

Protection class	IP20 according to DIN EN 60529
Vibration and shocks	according to DIN EN 50155
EMC	according to DIN EN 50121-3-2 and DIN EN 50155

### NOTE

Designation scheme	MTRS [1: GSM-R; +1: Data] [design] / [nominal input voltage] / optional: UIC / optional: IFS
System identification	MESA 23-07: including central unit (MTRS 1 RSS), operating unit(s) MMIS, handset(s), loudspeaker(s) and cables

## TECHNICAL DATA

### CLIMATIC CONDITIONS

Operating temperature range	-25 °C to +70 °C
Storage temperature range	-40 °C to +70 °C (in original package)
Maximal gradient	± 1 °C/min of ambient temperature
Maximal humidity	75 % in annual average
Relative humidity	95 % on max. 30 days per year
Altitude and pressure fluctuation	-100 m to 1800 m above sea level

### INTERFACES

Operating devices MMIS	2x 26-pin HD-D-Sub
Antenna connection	2x TNC female (1x option)
UIC line	25-pin D-Sub (option)
Digital input and output	15-pin HD-D-Sub
RS422	2x 15-pin HD-D-Sub (option)
Service, diagnostics	9-pin D-Sub; 6-pin Mini-DIN female (option)
Data radio	25-pin D-Sub (option)
Miscellaneous	power supply, protective earth conductor

